





One laboratory study gave subjects dimmable ceiling lighting and found that the control feature was well-used with positive results. The subjects who had the controllable lighting were more satisfied with the lighting, felt more comfortable in the room, rated the tasks as less difficult, and rated the lighting quality as higher than subjects who did not have control. Importantly, having the control system produced a 35 — 42% decrease in electrical consumption.⁵

A split lighting systems is also advantageous with regard to visual comfort and health since users can set the task environment to their preferences and tasks. Cornell studies have shown higher user satisfaction with uplighting than with conventional downlights especially with parabolic louvers (Hedge et al. 1989)

August 8-11, 2004


www.energy2004.ee.doe.gov




- Communication And Information Flow
- Effective Collaboration
- Adapting To Organizational & Technological Change
- Cultural Alignment Quality Of Work Life
- Image And Reputation
- Capacity For Innovation
- Attraction & Retention Of High Quality Workers
- Customer Satisfaction

August 8-11, 2004

www.energy2004.ee.doe.gov







- Facade: Use argon filled, low-e, low shading coefficient, good visible transmission, untinted glazing with 25% reduction in glass area throughout. Also consider AzurliteTM and EvergreenTM products with higher visible clarity than SungateTM with grey tint.
 Use interior upturned venetian blinds on south and north facades, with vertical blinds on east and west facades.
- Roof: Increase roof insulation to at least R-20 and ensure white (or very light) surface color.
- Lighting: Introduce to tenants the opportunity of modular and relocatable task-ambient lights with continuous dimming ballasts and user controls. Alternatively, introduce a split task-ambient lighting system with ambient uplighting system (appropriate to ceiling shape and reflectivity), with separate articulated arm task light.
 Select high efficiency T-5 lamps, high efficiency fixtures/reflectors, continuous dimming high energy efficiency ballasts, and user reconfigurable controls.
- HVAC: Introduce plenum floor based air system with distributed damper boxes, and the
 ability to add additional VAV zones for local requirements and tenant subdivisions.

August 8-11, 2004

www.energy2004.ee.doe.gov

2004 Ene 1919 Soffer Study Recommendations, cont'd

- . Energy Recovery: Use desiccant wheels in the roof-top air handling units.
- Networking: Introduce a structured wiring system for power, and for data/voice under a
 raised floor, with ability to relocate and add outlet boxes as needed.
- Equipment Power loads: Promote Energy Star ratings for tenants, illustrating the costsavings from 1 to 3 W·ft⁻² of plug loads.
- Modular components: Utilize modular, plug and play components rather than redundancies or embedded solutions for HVAC, connectivity and lighting, as well as carpets (must be same size as access floor).
- Reconfigurable furniture: Promote relocatable walls and horizontally and vertically stackable furniture to support tenant reconfigurations without waste.
- Benign materials: Promote low outgassing and environmentally responsible fabrics, carpets, acoustic ceilings. Avoid paints and adhesives.

August 8-11, 2004

www.energy2004.ee.doe.gov





